

CP745es

A Bright Idea

To inspire audiences in schools, boardrooms or general business settings, presenters often turn to the CP745es. This cost-effective solution delivers true, bright light and superior color reproduction for virtually any type of presentation.



CP745es

Specifications



BRIGHTNESS

2600 Lumens (Standard)

2100 Lumens (Economy)

RESOLUTION

1024 x 768 XGA (Native)

1280 x 1024 SXGA (Supported)

DISPLAY TYPE

0.63" HTPS TFT LCD x 3

CONTRAST RATIO

500:1

ASPECT RATIO

4:3 Native

16:9 Compatible

THROW RATIO

1.45 ~ 1.74 (x screen width)

PROJECTION LENS

Manual Zoom & Focus

ZOOM RATIO

1:1.2

DIAGONAL IMAGE SIZE

40" - 300"

THROW DISTANCE

4' - 30'

KEystone

+/- 30° Vertical

LAMP

180 watt NSH

LAMP LIFE

2000 hours (Standard)

3000 hours (Economy)

INPUTS

VGA (Computer 2/YpBPr)

VGA Computer 1

S-Video

Composite Video

Audio (3.5 mm)

OUTPUTS

Audio (3.5 mm)

VGA

PROJECTOR CONTROLS

USB

RS232 (DIN)

COMPATIBILITY

VGA, SVGA, XGA, SXGA, MAC

EDTV / SDTV / HDTV

480i/p, 576i/p, 720p, 1080i

FCC CERTIFICATION

FCC-B, UL, TUV-CB, c-UL, CB, CE, CCC

VIDEO COMPATIBILITY

NTSC, NTSC 4.43, PAL B/G/H/V/M/N 60, SECAM

AUDIO

1 x 2w Mono Speaker

DECIBEL RATING

33 dB (Standard)

30 dB (Economy)

H-SCAN FREQUENCY

15-69 kHz

V-REFRESH RATE

43-85 kHz

POWER SUPPLY

AC 100-240 Volts (50-60Hz)

POWER CONSUMPTION

250 Watts

DIMENSIONS (WxDxH)

12.2" x 10.6" x 3.8"

WEIGHT

6.8 lbs

WARRANTY

3 Year Parts & Labor / 90 Day Lamp

Special features of the CP745es include:

3-D Comb Filtering—
Eliminates artifacts resulting in better video quality.

Auto Brightness—
Detects ambient light and adjusts brightness, extending lamp life.

Business Card Holder—
Mark your territory with a convenient slot to hold your business card!

Auto Keystone Correction—
Projector will automatically correct a trapezoidal image.

Unplug & Go—
No need to wait for the projector to cool down. Just unplug and go!

